

MATERIAL SAFETY DATA SHEET

– –		•	\ <u>//</u> шм	IS - CLASSIFICATION	•		
	OLOMITI YDRATE	-	D2A: MATERIALS CAUSING OTHER TOXIC EFFECTS E: CORROSIVE MATERIAL				
MANUFACTURER'S AND	SUPPLIEF	R'S NAME:					
GRAYMONT DOLIME (OH) INC		218	380 West, State, Route16	3, Genoa, Ohio 43430.			
GRAYMONT WESTERN LIME INC	•	206	6 N. 6 th Avenue, West Ber	nd, Wisconsin, 53095			
EMERGENCY TEL. No.	: (613) 9	96 – 6666 CAN	UTEC (Canada) (8	00) 424 – 9300 CHEM	ITREC (US)		
Chemical Name		Chemical Family	ily Chemical Formula				
Calcium Magnesium Hydroxide Oxide and Calcium Magnesium Hydroxide		Alkaline earth hydroxide		Complex mixture – mostly CaMg(OH)₄ and Ca(OH)₂MgO			
Molecular Weight		Trade Name and Synonyms N		Material Use			
CaMg(OH) ₄ = 132. Ca(OH) ₂ MgO = 114		(Ca(OH)₂Mg	d dolomitic lime O), Double hydrated lime (CaMg(OH)₄)	Neutralization, Flocculation, Stabilization, Polishing, Masonry Mortar, Plaster, Stucco, Fresco Paints and Lime wash.			
PRODUCT NAME		I		FORMULA	CAS#		
BONDCRETE [®] Mason's L	.ime			CaMg(OH) ₄	39445-23-3		
Graymont Dolomitic Hydi	rated Agri	cultural Lime		Ca(OH)₂MgO	58398-71-3		
Graymont Dolomitic Hydi	rated Lime	e		Ca(OH)₂MgO	58398-71-3		
Graymont Dolomitic Spra	ıy Lime			CaMg(OH)₄	39445-23-3		
GRAND PRIZE [®] Finish Li	me			Ca(OH)₂MgO	58398-71-3		
HI-MAG-CHEM [®] Hydrate				Ca(OH)₂MgO	58398-71-3		
IVORY [®] Autoclaved Finis	h Lime	CaMg(OH)₄	39445-23-3				
KEMIDOL [®] Hydrate				Ca(OH)₂MgO	58398-71-3		
KEMIDOL [®] Superhydrate				CaMg(OH)₄	39445-23-3		
LIMOID [®] Type "N" Hydrat	te	Ca(OH)₂MgO	58398-71-3				
LIMOID [®] Type "S" Hydrat	e	CaMg(OH)₄	39445-23-3				
MORTASEAL [®] Autoclave	d Mason's	CaMg(OH)₄	39445-23-3				
SNOWDRIFT [®] Autoclaved	d Finish Li	CaMg(OH)₄	39445-23-3				
SUPER LIMOID [®] Agricult	ural Hydra	Ca(OH)₂MgO	58398-71-3				
SUPER LIMOID [®] Mason's	Hydrated	CaMg(OH)₄	39445-23-3				
SUPER LIMOID [®] Mason's	Hydrated	CaMg(OH)₄	39445-23-3				
WESTERN LIMATE – Indu	ustrial Gra	CaMg(OH)₄	39445-23-3				
WESTERN MIRACLE LIM	E – Type S	CaMg(OH)₄	39445-23-3				
WESTERN Air Entrained	l imo _ Tv	e CaMg(OH) ₄	39445-23-3				
WESTERN FINISH LIME -	-	-			00440 20 0		

Hazardous Ingredients	Approximate Concentration	C.A.S. Number	Exposure limits (mg/m ³)					
			OSHA PEL	ACGIH TLV	RSST VEMP	MSHA PEL	NIOSH REL	NIOSH IDLH
(Complex Mixture)	(% by weight)		(TWA) 8/40h	(TWA) 8/40h	(TWA) 8/40h	(TWA) 8/40h	(TWA) 10/40h	
Calcium Magnesium Hydroxide	60 to 100	39445-23-3	N/A	N/A	N/A	N/A	N/A	N/A
Calcium Magnesium Hydroxide Oxide	60 to 100	58398-71-3	N/A	N/A	N/A	N/A	N/A	N/A
Calcium hydroxide	30 to 60	1305-62-0	15 (tot dust) 5 resp dust	5	5	5	N/A	N/A
Magnesium Hydroxide	0 to 40	1309-42-8	N/A	N/A	N/A	N/A	N/A	N/A
Magnesium Oxide	0 to 40	1309-48-4	10	10	10	10	N/A	N/A
Crystalline Silica, Quartz	0 à 0.1 Or 0.1 à 1 (Note 1)	14808-60-7	30/(%SiO ₂)+2 (T) 10/(%SiO ₂)+2 (R)	0.025 (R)	0.1 (R)	30/(%SiO ₂)+2 (T) 10/(%SiO ₂)+2 (R)	0.05 (R)	50

(Note 1): Concentration of crystalline silica in a series of lime products will vary from source to source. It was not detected on some samples (< 0.1% w/w). Therefore two ranges are being disclosed. (Note 2): ACGIH TLV Version 1973 has been adopted by the Mine Safety Health Administration (MSHA) as the regulatory Exposure Standard. (Note 3): (T) Total Dust; (R): Respirable Dust.

SECTION III - PHYSICAL AND CHEMICAL DATA						
Physical State	Odor and Appearance		Odor Threshold (p.p.m.)	Specific Gravity		
Gas □ Liquid □ Solid ☑	Slight earthy odor – F	ine white powder	Not applicable	2.2 - 2.6		
Vapor Pressure (mm)	Vapor Density (Air = 1) Evaporation Rate		Boiling Point (°C)	Melting Point (°C)		
Not applicable	Not applicable	Not applicable	Decomposes at 345	Not applicable		
Solubility in Water (20°C)	r (20°C) Volatiles (% by volume) pH (25 °C)		Bulk Density (kg/m ³)	Coefficient of water/oil distribution		
0.1g/100g Solution	Not applicable	Sat. solution Ca(OH) ₂ 12.45	400 - 650	Not applicable		

SECTION IV - FIRE OR EXPLOSION HAZARD DATA Flammability Yes 🗆 No 🗹 If yes, under which conditions? **Extinguishing Media** Dolomitic Hydrated Lime does not burn. Use extinguisher appropriate for material burning. **Special Fire Fighting Procedures** Not applicable Flash point (°C) and Method Upper flammable limit (% by volume) Lower flammable limit (% by volume) Not applicable Not applicable Not applicable Auto Ignition Temperature (°C) **TDG Flammability Classification** Hazardous Combustion Products Not applicable Non-flammable None **Dangerous Combustion Products** None **EXPLOSION DATA** Sensitivity to Chemical Impact Rate of Burning **Explosive Power** Sensitivity to Static Discharge Not applicable Not applicable Not applicable Not applicable

SECTION V - REACTIVITY DATA					
Chemical Stability Yes ፼ No □	If no, under which conditions?	Absorbs carbon dioxide in the air to form calcium magnesium carbonate.			
Incompatibility to of	ther substances				
Yes ☑ No □	If so, which ones?	Boron tri-fluoride, chlorine tri-fluoride, ethanol, fluorine, hydrogen fluoride, phosphorus pentoxide; water and acids (violent reaction with generating heat and possible explosion in confined area).			
Reactivity Yes ⊠ No □	If so, under which conditions?	Reacts violently with Maleic Anhydride, strong acids. Reacts chemically with acids and many other compounds and chemical elements to form calcium and magnesium based compounds. Explosive when mixed with nitro organic compounds.			
Hazardous Decomposition Products		Calcium Hydroxide decomposes at 540°C and Magnesium Hydroxide decomposes at 345°C to produce calcium oxide, magnesium oxide and water.			
Hazardous Polymerization Products		Will not occur.			

SECTION VI - TOXICOLOGICAL PROPERTIES Route of Entry ☑ Skin Contact □ Skin Absorption ☑ Eve Contact ☑ Acute □ Chronic Inhalation ☑ Ingestion Inhalation Effects of Acute Exposure to Product Skin Severe irritation of mucous and skin, removes natural skin oils. Eyes Severe eye irritation, intense watering of the eyes, possible lesions, possible blindness when exposed for prolonged period. Eye Irritation Data: Eye-Rabbit-10mg/ 24 h - Severe. Inhalation If inhaled in form of dust, irritation of breathing passages, cough, sneezing. Ingestion If ingested: pain, vomiting blood, diarrhea, collapse, drop in blood pressure (indicates perforation of esophagus or stomach). Effects of Chronic Exposure to Product: Contact dermatitis. Following repeated or prolonged contact, this product can cause redness, desquamation and fissures. This product may contain trace amounts of crystalline silica. Excessive inhalation of respirable crystalline silica dust may result in respiratory disease, including silicosis, pneumoconiosis and pulmonary fibrosis. LD₅₀ of Product (Specify Species and Route) Irritancy of Product Exposure limits of Product Unavailable Severe to moist tissues Unavailable LC₅₀ of Product (Specify Species) Sensitization to Product Synergistic materials Unavailable None None reported ☑ Carcinogenicity □ Reproductive effects □ Tératogenicity □ Mutagenicity Dolomitic Hydrated Lime is not listed as a carcinogen by ACGIH, MSHA, OSHA, NTP, DFG, RSST or IARC. It may, however, contain trace amounts of Crystalline Silica listed carcinogens by these organizations. Crystalline Silica, which inhaled in the form of quartz or crystobalite from occupational sources, is classified by IARC as carcinogenic to humans. (Group 1) Silica, crystalline (Airborne particles of respirable size) is regulated under California's Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65). Crystalline Silica is listed as a chemical known to the State to cause cancer. NIOSH considers crystalline silica to be potential occupational carcinogen as defined by the OSHA carcinogen policy [29 CFR 1990]. (Ca). NTP lists respirable Crystalline Silica as known to be human carcinogens based on sufficient evidence of carcinogenicity in humans. (K). ACGIH lists respirable Crystalline Silica (quartz) as suspected human carcinogen. (A2). DFG lists respirable Crystalline Silica as a substance that causes cancer in man (1) RSST lists respirable Crystalline Silica (guartz) as suspected human carcinogen.

SECTION VII - PREVENTI	VE MEASURES			
Personal Protective Equipment (PPE)	Wear clean, dry gloves, full length pants over boots, long sleeved shirt buttoned at the neck, head protection and approved eye protection selected for the working conditions.			
Gloves (Specify)	Gauntlets Cuff style.			
Respiratory (Specify)	 Respirator Recommendations for Dolomitic Hydrated Lime: Not available. Respirator Recommendations for Calcium Oxide: NIOSH approved respirator. <u>Up to 10 mg/m³</u>: (APF = 5) Any quarter-mask respirator. <u>Up to 20 mg/m³</u>: (APF = 10) Any particulate respirator equipped with an N95, R95 or P95 filter except quarter-mask respirator. Any supplied-air respirator. <u>Up to 25 mg/m³</u>: (APF = 25) Any supplied-air respirator operated in a continuous- flow mode. Any powered, air purifying respirator with a high-efficiency particulate filter. 			
Eyes (Specify)ANSI, CSA or ASTM approved safety glasses with side shields. Tight fitting dust goggles should be worn when excessive (visible) dust conditions are present. D not wear contact lenses without tight fitting goggles when handling this chemic				
Footwear (Specify)	Resistant to caustics.			
Clothing (Specify)	Fully covering skin. Remove when wet or contaminated. Change daily.			
Other (Specify)	Evaluate degree of exposure and use PPE if necessary. After handling lime, employees must shower. If exposed daily, use oil, Vaseline, silicone base crème etc. to protect exposed skin, particularly neck, face and wrists.			
Engineering Controls (e.g. ventil	ation, enclosed process, specify)			
Enclose dust sources; us Concentration Permitted.	e exhaust ventilation (dust collector) at handling points, keep levels below Max.			
Leak and Spill Procedure				
Limit access to trained pers	sonnel. Use industrial vacuums for large spills. Ventilate area.			
Waste Disposal				
Transport to disposal area	or bury. Review Federal, Provincial and local Environmental regulations.			
Handling Procedures and Equip	ment			
ventilation, use NIOSH ap	ct. Minimize dust generation. Wear protective goggles and in cases of insufficient proved dust respirator. An eye wash station and safety shower should be readily rial or its water dispersions are used. Contact lenses should not be worn when			
Storage Requirements				
Keep tightly closed contai children.	ners in a cool, dry and well ventilated area, away from acids. Keep out of reach of			
Special Shipment Information				
	is not regulated by the Transportation of Dangerous Goods (TDG) Regulations s Materials Regulations (USA).			

SECTION VIII - FIRST AID MEASURES

Skin

Carefully and gently brush the contaminated body surfaces in order to remove all traces of lime. Use a brush, cloth or gloves. Remove all lime-contaminated clothing. Rinse contaminated area with lukewarm water for 15 to 20 minutes. Consult a physician if exposed area is large or if irritation persists.

Eyes

Immediately rinse contaminated eye(s) with gently running lukewarm water (saline solution is preferred) for 15 to 20 minutes. In the case of an embedded particle in the eye, or chemical burn, as assessed by first aid trained personnel, contact a physician.

Inhalation

Move source of dust or move victim to fresh air. Obtain medical attention immediately. If victim does not breathe, give artificial respiration.

Ingestion

If victim is conscious, give 300 ml (10 oz) of water, followed by diluted vinegar (1 part vinegar, 2 parts water) or fruit juice to neutralize the alkali. Do not induce vomiting. Contact a physician immediately.

General Advise

Consult a physician for all exposures except minor instances of inhalation.

SECTION IX - REGULATORY INFORMATION

Superfund Amendments and Reauthorization Act of 1986 (SARA Title III). / The Emergency Planning and "Community Right-to-Know" Act (EPCRA). / Comprehensive Environmental Response, Compensation and Liability Act (CERCLA). / Resource Conservation and Recovery Act (RCRA).

Component Dolomitic Hydrated Lime has been reviewed against the following regulatory listings:

- SARA Section 302 Emergency Planning Notification. Extremely Hazardous Substances (EHS) List and Threshold Planning Quantity (TPQ). (40 CFR, Part 355, Section 30): <u>Not listed</u>.
- SARA Section 304 Emergency Release Notification. Extremely Hazardous Substances (EHS) and Reportable Quantity (RQ) List. (40 CFR, Part 355, Section 40): <u>Not listed</u>.
- SARA Section 311/312 Hazard Categories (40 CFR, Part 370): This product is regulated under CFR 1910.1200 (OSHA Hazard Communication) as Immediate (Acute) Health Hazards Irritant.
- SARA Section 313 Toxics Release Inventory (TRI). Toxic Chemical List (40 CFR, Part 372). Not listed.
- CERCLA Hazardous Substance (40 CFR, Part 302): Not listed in Table 302.4.
- RCRA Hazardous Waste Number (40 CFR, Part 261, Subpart D): Not listed.
- RCRA Hazardous Waste Classification (40 CFR, Part 261, Subpart C): Not classified.

CWA 311. - Clean Water Act List of Hazardous Substances.

Dolomitic Hydrated Lime does not appear on the Clean Water Act (CWA) list of hazardous substances.

California Proposition 65.

Component Calcium Magnesium Hydroxide does not appear on the above regulatory listing. This product may contain small amounts of crystalline silica. Silica, crystalline (Airborne particles of respirable size) is regulated under California's Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65). Crystalline Silica is listed as a chemical known to the State to cause cancer.

Transportation - Hazardous Materials Regulations (USA) & Transportation of Dangerous Goods (TDG) Regulations (Can).

Dolomitic Hydrated Lime does not appear on the above regulatory listings.

Toxic Substances Control Act (TSCA).

All naturally occurring components of this product are automatically included in the USEPA TSCA Inventory List per 40 CFR 710.4 (b). All other components are listed on the USEPA TSCA Chemical Substances Inventory. Dolomitic Hydrated Lime is subject to inventory update reporting (IUR).

Canadian Environmental Protection Act (CEPA) – Substances Lists (DSL/NDSL).

Dolomitic Hydrated Lime (Calcium Magnesium Hydroxide & Calcium Magnesium Hydroxide Oxide) is specified on the Non-Domestic Substances List (NDSL).

ANSI/NSF 60 - Drinking Water Treatment Additives.

Not applicable

FDA - U.S. Food and Drug Administration, Department of Health and Human Services.

Not applicable

section.

SECTION X - OTHER INFORMATION							
Hazardous Materials Identification System (U.S.)	HMIS® HMIS® <td< td=""><td></td><td>Hire Protection tion (U.S.) 04 Health Hazard</td><td>Fire Hazard</td></td<>		Hire Protection tion (U.S.) 04 Health Hazard	Fire Hazard			
WHMIS – Classificatior):		WHMIS – Classification:				
"E" Corrosive Materia	ıls.		"D2A" Materials causing other toxic effects.				
Symbol:		Symbol:					
Additional Information/Comments: The technical data contained herein is given as information only and is believed to be reliable. GRAYMONT makes no guarantee of results and assumes no obligation or liability in connection therewith.							
Sources Used: NFPA, NLA, TDG, CSST, RSST, (LSRO-FASEB), Hazardous Products Act, Environment Canada, Enviroguide, OSHA, ACGIH, IARC, NIOSH, CFR, NTP, HSDB, EPA SRS, RTECS, DFG, Chemistry and Technology of Lime and Limestone (John Wiley and Sons, Inc.), Lime and Limestone (WILEY-VCH).							
SECTION XI - PREPARATION INFORMATION							
Prepared by:			Telephone number:	Date :			
GRAYMONT (QC) IN	C .						
Quality Assura	nce & Technical Servic	es	(450) 449-2262	August 2012			
An electronic version of this MSDS is available at: <u>www.graymont.com</u> under the PRODUCTS							