

MasterLife[®] SF 100

Densified Silica Fume Mineral Admixture

Formerly Rheomac SF 100*

Description

MasterLife SF 100 dry, densified silica fume admixture is formulated to produce extremely strong, durable concrete. MasterLife SF 100 silica fume admixture meets the requirements of ASTM C 1240, Standard Specification for Silica Fume used in Cementitious Mixtures.

Applications

Recommended for use in:

- Steel-reinforced concrete structures or wet shotcrete applications exposed to deicing or airborne salts
- Any construction project requiring the protection provided by highly durable, low permeability concrete
- Projects requiring high-strength/high-performance concrete
- Green Sense[®] Concrete

Features

- Added cohesiveness
- Reduced bleeding
- Enhanced performance


Benefits

- Increased concrete service life
- Increased strength
- Increased modulus of elasticity
- Reduced permeability thereby increasing durability
- Increased resistance to sulfate attack
- Increased resistance to alkali-silica reactivity


Performance Characteristics

Permeability: MasterLife SF 100 silica fume admixture is a micro-filling material that physically fills the voids between cement particles. MasterLife SF 100 silica fume admixture dramatically lowers permeability and reduces the size and number of capillaries that allow contaminants to enter the matrix.

Rapid Chloride Permeability



Typical Compressive Strengths



Compressive Strength: As a pozzolan, MasterLife SF 100 silica fume admixture reacts chemically within a cementitious matrix to increase the amount of calcium silicate hydrate (CSH) gel that is formed. The CSH gel is the bonding agent that holds the matrix of a cementitious mixture together in the hardened state. The additional CSH gel increases strength and decreases permeability.

Specific Gravity: The specific gravity of MasterLife SF 100 silica fume admixture is 2.2.

Guidelines for Use

Dosage: MasterLife SF 100 silica fume admixture is recommended for use in concrete and wet shotcrete applications at an addition dosage of 5-15% by mass of cement.

Dispensing and Mixing: For concrete and wet shotcrete, MasterLife SF 100 silica fume admixture is batched at the concrete production plant in a manner similar to that for cement or other cementitious materials such as fly ash. It may be batched in a central or truck mixer. Follow the procedures outlined in ASTM C 94/C 94M, Standard Specification for Ready-Mixed Concrete or refer to the Silica Fume Association Users Manual for specific batching and mixing instructions.

Product Notes

Corrosivity – Non-Chloride, Non-Corrosive: MasterLife SF 100 silica fume admixture will neither initiate nor promote corrosion of reinforcing or prestressing steel embedded in concrete or of galvanized steel floor and roof systems. Neither calcium chloride nor other chloride-based ingredients are used in the manufacture of this silica fume.

Compatibility: MasterLife SF 100 silica fume admixture can be used with portland cements approved under ASTM, AASHTO or CRD specifications. It is compatible with most concrete admixtures, including all BASF admixtures. MasterLife SF 100 silica fume admixture is recommended for use with high-range water-reducing admixtures, such as the MasterGlenium® series, for maximum workability while maintaining a low water-cementitious materials ratio.

Storage and Handling

MasterLife SF 100 silica fume admixture stores, handles and dispenses similar to cement or fly ash. In bulk, MasterLife SF 100 silica fume admixture may be stored in a silo. Refer to the Silica Fume Association Users Manual for information on the appropriate set up for pumping and handling silica fume into silos. Packaged MasterLife SF 100 silica fume admixture must be stored in a dry area. MasterLife SF 100 silica fume admixture requires no special dispensing equipment.

Shelf Life: MasterLife SF 100 silica fume admixture has a minimum shelf life of 24 months. Depending on storage conditions, the shelf life may be greater than stated. Please contact your local sales representative regarding suitability for use and dosage recommendations if the shelf life of MasterLife SF 100 silica fume admixture has been exceeded.

Packaging

MasterLife SF 100 silica fume admixture is available in 25 lb (11.34 kg) shreddable bags, 2,000 lb (907 kg) bulk bags or by bulk delivery.

Related Documents

Safety Data Sheet: MasterLife SF 100 silica fume admixture, Silica Fume Association Users Manual.

Additional Information

For additional information on MasterLife SF 100 silica fume admixture or its use in developing concrete mixtures with special performance characteristics, contact your local sales representative.

The Admixture Systems business of BASF's Construction Chemicals division is the leading provider of solutions that improve placement, pumping, finishing, appearance and performance characteristics of specialty concrete used in the ready-mixed, precast, manufactured concrete products, underground construction and paving markets. For over 100 years we have offered reliable products and innovative technologies, and through the Master Builders Solutions brand, we are connected globally with experts from many fields to provide sustainable solutions for the construction industry.

Limited Warranty Notice

BASF warrants this product to be free from manufacturing defects and to meet the technical properties on the current Technical Data Guide, if used as directed within shelf life. Satisfactory results depend not only on quality products but also upon many factors beyond our control. **BASF MAKES NO OTHER WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE WITH RESPECT TO ITS PRODUCTS.** The sole and exclusive remedy of Purchaser for any claim concerning this product, including but not limited to, claims alleging breach of warranty, negligence, strict liability or otherwise, is shipment to purchaser of product equal to the amount of product that fails to meet this warranty or refund of the original purchase price of product that fails to meet this warranty, at the sole option of BASF. Any claims concerning this product must be received in writing within one (1) year from the date of shipment and any claims not presented within that period are waived by Purchaser. **BASF WILL NOT BE RESPONSIBLE FOR ANY SPECIAL, INCIDENTAL, CONSEQUENTIAL (INCLUDING LOST PROFITS) OR PUNITIVE DAMAGES OF ANY KIND.**

Purchaser must determine the suitability of the products for the intended use and assumes all risks and liabilities in connection therewith. This information and all further technical advice are based on BASF's present knowledge and experience. However, BASF assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights, nor shall any legal relationship be created by or arise from the provision of such information and advice. BASF reserves the right to make any changes according to technological progress or further developments. The Purchaser of the Product(s) must test the product(s) for suitability for the intended application and purpose before proceeding with a full application of the product(s). Performance of the product described herein should be verified by testing and carried out by qualified experts.

* Rheomac SF 100 became MasterLife SF 100 under the Master Builders Solutions brand, effective January 1, 2014.

© BASF Corporation 2016 ■ 03/16 ■ PRE-DAT-0091

BASF Corporation
Admixture Systems
www.master-builders-solutions.basf.us

United States
23700 Chagrin Boulevard
Cleveland, Ohio 44122-5544
Tel: 800 628-9990 ■ Fax: 216 839-8821

Canada
1800 Clark Boulevard
Brampton, Ontario L6T 4M7
Tel: 800 387-5862 ■ Fax: 905 792-0651