SAFETY DATA SHEET



Issuing Date 11-Nov-2014 Revision date 10-Aug-2018

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product identifier

Product Name Sure Klean® Weather Seal Blok-Guard® & Graffiti Control

Other means of identification

Product Code(s) 40093 UN number UN1866

Recommended use of the chemical and restrictions on use

Recommended use Restricted to professional users.
Uses advised against No information available

Details of the supplier of the safety data sheet

Manufacturer Address

PROSOCO, Inc. 3741 Greenway Circle Lawrence, Kansas 66046

Emergency telephone number

8:00 AM – 5:00 PM CST Monday-Friday NON-BUSINESS HOURS (INFOTRAC)785-865-4200
800-535-5053

2. HAZARDS IDENTIFICATION

Classification

Skin corrosion/irritation	Category 2
Serious eye damage/eye irritation	Category 2A
Carcinogenicity	Category 2
Aspiration hazard	Category 1
Flammable liquids	Category 3

Label elements

Emergency Overview

Warning

Hazard statements

Causes skin irritation
Causes serious eye irritation
Suspected of causing cancer
May be fatal if swallowed and enters airways
Flammable liquid and vapor



Appearance clear Physical state Liquid Odor Petroleum

Precautionary Statements - Prevention

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Wear eye/face protection

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/ /equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

If skin irritation occurs: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Acetic acid vapors form as by-product following hydrolysis reaction with water or humid air.

Other information

- May be harmful if swallowed
- · May be harmful in contact with skin

No information available

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No.	Weight-%	Trade Secret
Mineral Spirits	64742-88-7	60 - 100	*
Polydimethyl siloxane diol	70131-67-8	5 - 10	*
1,2,4-trimethylbenzene	95-63-6	3 - 7	*
Xylene	1330-20-7	1 - 5	*
Cumene	98-82-8	0.1 - 1	*
Ethylbenzene	100-41-4	0.1 - 1	*

^{*} The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General advice In case of accident or unwellness, seek medical advice immediately (show directions for

use or safety data sheet if possible).

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and

continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If symptoms

persist, call a physician.

Skin Contact Wash off immediately with soap and plenty of water. If skin irritation persists, call a

physician.

InhalationMove to fresh air in case of accidental inhalation of vapors or decomposition products. If

breathing is irregular or stopped, administer artificial respiration. Avoid direct contact with

skin. Use barrier to give mouth-to-mouth resuscitation. Call a physician.

Ingestion Do NOT induce vomiting. Clean mouth with water and drink afterwards plenty of water.

Never give anything by mouth to an unconscious person. Call a physician or poison control

center immediately.

Self-protection of the first aider Remove all sources of ignition. Use personal protective equipment as required.

Most important symptoms and effects, both acute and delayed

Symptoms May be fatal if swallowed and enters airways. May be harmful if inhaled. May be harmful if

swallowed. Irritating to eyes and skin.

Indication of any immediate medical attention and special treatment needed

Note to physiciansTreat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use. Dry chemical. Carbon dioxide (CO2). Water spray (fog). Foam. Alcohol resistant foam.

Unsuitable Extinguishing Media Caution: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

Keep product and empty container away from heat and sources of ignition. Risk of ignition.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate

ventilation, especially in confined areas. Keep people away from and upwind of spill/leak. Pay attention to flashback. Take precautionary measures against static discharges. Use

personal protective equipment as required.

Environmental precautions

Environmental precautions Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do

not allow into any sewer, on the ground or into any body of water. See Section 12 for

additional ecological information.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so. Dike far ahead of liquid spill for later

disposal.

Methods for cleaning up

Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers. Take precautionary measures against static discharges. Use only non-sparking tools. Ground and bond containers when transferring material.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

Ensure adequate ventilation, especially in confined areas. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Take precautionary measures against static discharges. Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded. Use with local exhaust ventilation. Do not smoke. Use personal protection recommended in Section 8.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep tightly closed in a dry and cool place. Keep in properly labeled containers. Keep away

from heat. Keep out of the reach of children.

Incompatible materials Incompatible with oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
1,2,4-trimethylbenzene 95-63-6			TWA: 25 ppm TWA: 125 mg/m ³
Xylene 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m³	
Cumene 98-82-8	TWA: 50 ppm	TWA: 50 ppm TWA: 245 mg/m³ (vacated) TWA: 50 ppm (vacated) TWA: 245 mg/m³ (vacated) S* S*	IDLH: 900 ppm TWA: 50 ppm TWA: 245 mg/m³
Ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m³ STEL: 125 ppm STEL: 545 mg/m³

NIOSH IDLH Immediately Dangerous to Life or Health

Other information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962

(11th Cir., 1992).

Appropriate engineering controls

Engineering Controls Showers

Eyewash stations

Ventilation systems. Ground/bond container and receiving equipment.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear protective gloves and protective clothing.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

ASTM D 3278

provided in accordance with current local regulations.

General Hygiene Considerations When using do not eat, drink or smoke. Regular cleaning of equipment, work area and

clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Liquid
Appearance clear Odor Petroleum

Color colorless Odor threshold No information available

PropertyValuesRemarks • MethodpHNot ApplicableNot Applicable

pH Not Applicable
Melting point / freezing point °F Not Applicable
-30 °C / -22 °F

Boiling point / boiling range No information available

Flash point 38 °C / 100 °F

Evaporation rate No information available Flammability (solid, gas) No information available

Flammability (solid, gas) No informat Flammability Limit in Air

Upper flammability limit:
Lower flammability limit:
Vapor pressure
Vapor density

No information available
No information available
No information available

Specific gravity .802 Water solubility negligible

Solubility in other solvents
Partition coefficient
Autoignition temperature
Decomposition temperature
Kinematic viscosity
No information available

Explosive properties
Oxidizing properties
Not Applicable
Not Applicable

10. STABILITY AND REACTIVITY

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

None under normal processing.

Conditions to avoid

Heat, flames and sparks.

40093 Sure Klean® Weather Seal Blok-Guard® & Graffiti Control

Incompatible materials

Incompatible with oxidizing agents.

Hazardous decomposition products

Acetic acid. silicon dioxide. Carbon oxides. Unidentified organic compounds.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information May be fatal if swallowed and enters airways May be harmful by inhalation, ingestion, or

skin absorption

Inhalation Avoid breathing vapors or mists. May be harmful if inhaled. Aspiration into lungs can

produce severe lung damage.

Eye contact Avoid contact with eyes. May cause irritation.

Skin Contact Avoid contact with skin. May be absorbed through the skin in harmful amounts. May cause

irritation.

Ingestion Do not taste or swallow. May be fatal if swallowed. Potential for aspiration if swallowed.

Component Information

Chemical name	LD50/Oral	LD50/Dermal	Inhalation LC50
Mineral Spirits 64742-88-7	> 5000 mg/kg (Rat)	= 3000 mg/kg (Rabbit)	> 5.28 mg/L (Rat) 4 h
1,2,4-trimethylbenzene 95-63-6	= 3400 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 18 g/m³ (Rat) 4 h
Xylene 1330-20-7	= 4300 mg/kg (Rat)	> 1700 mg/kg (Rabbit)	= 5000 ppm (Rat) 4 h = 47635 mg/L (Rat) 4 h
Cumene 98-82-8	= 1400 mg/kg (Rat)	> 3160 mg/kg (Rabbit)	= 39000 mg/m³ (Rat) 4 h
Ethylbenzene 100-41-4	= 3500 mg/kg (Rat)	= 15354 mg/kg (Rabbit)	= 17.2 mg/L (Rat) 4 h

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms May be fatal if swallowed and enters airways. May be harmful if inhaled. May be harmful if

swallowed. Irritating to eyes and skin.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization Germ cell mutagenicityNo information available.
No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Xylene	-	Group 3	-	-
1330-20-7				
Cumene	-	Group 2B	-	X
98-82-8		•		
Ethylbenzene	A3	Group 2B	-	X
100-41-4		•		

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Group 3 - Not Classifiable as to Carcinogenicity in Humans

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity

STOT - single exposure

No information available.

No information available.

40093 Sure Klean® Weather Seal Blok-Guard® & Graffiti Control

STOT - repeated exposureNo information available.

Chronic toxicity May cause adverse effects on the bone marrow and blood-forming system.

Target organ effects central nervous system, Eyes, Respiratory system, Skin, blood.

Aspiration hazard May be fatal if swallowed and enters airways.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 4172 mg/kg
ATEmix (dermal) 2753 mg/kg mg/l
ATEmix (inhalation-dust/mist) 17.5 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Chemical name Algae/aquatic plant	s Fish	Toxicity to	Crustacea
		microorganisms	
Mineral Spirits 450: 96 h	800: 96 h Pimephales	-	100: 48 h Daphnia magna
64742-88-7 Pseudokirchneriella	ı · · · · · · · · · · · · · · · · · · ·		mg/L EC50
subcapitata mg/L EC5			
1,2,4-trimethylbenzene -	7.19 - 8.28: 96 h Pimephales	-	6.14: 48 h Daphnia magna
95-63-6	promelas mg/L LC50		mg/L EC50
	flow-through		
Xylene -	13.4: 96 h Pimephales	-	3.82: 48 h water flea mg/L
1330-20-7	promelas mg/L LC50		EC50 0.6: 48 h Gammarus
	flow-through 2.661 - 4.093:		lacustris mg/L LC50
	96 h Oncorhynchus mykiss		
	mg/L LC50 static 13.5 - 17.3:		
	96 h Oncorhynchus mykiss		
	mg/L LC50 13.1 - 16.5: 96 h		
	Lepomis macrochirus mg/L		
	LC50 flow-through 19: 96 h		
	Lepomis macrochirus mg/L		
	LC50 7.711 - 9.591: 96 h		
	Lepomis macrochirus mg/L		
	LC50 static 23.53 - 29.97: 96		
	h Pimephales promelas mg/L LC50 static 780: 96 h		
	Cyprinus carpio mg/L LC50		
	semi-static 780: 96 h		
	Cyprinus carpio mg/L LC50		
	30.26 - 40.75: 96 h Poecilia		
	reticulata mg/L LC50 static		
Cumene 2.6: 72 h	6.04 - 6.61: 96 h Pimephales	_	0.6: 48 h Daphnia magna
98-82-8 Pseudokirchneriella		-	mg/L EC50 7.9 - 14.1: 48 h
subcapitata mg/L EC5	3		Daphnia magna mg/L EC50
Subcapitata mg/E Eos	Oncorhynchus mykiss mg/L		Static
	LC50 flow-through 2.7: 96 h		Giano
	Oncorhynchus mykiss mg/L		
	LC50 semi-static 5.1: 96 h		
	Poecilia reticulata mg/L		
	LC50 semi-static		
Ethylbenzene 4.6: 72 h	11.0 - 18.0: 96 h	-	1.8 - 2.4: 48 h Daphnia
100-41-4 Pseudokirchneriella			magna mg/L EC50
subcapitata mg/L EC50			
96 h Pseudokirchnerie			
subcapitata mg/L EC50			
11.3: 72 h	96 h Pimephales promelas		
Pseudokirchneriella			
subcapitata mg/L EC5			
static 1.7 - 7.6: 96 h			
Pseudokirchneriella	96 h Pimephales promelas		
subcapitata mg/L EC5	mg/L LC50 static 9.6: 96 h		
static	Poecilia reticulata mg/L		

40093 Sure Klean® Weather Seal Blok-Guard® & Graffiti Control

ſ		LC50 static	

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Chemical name	Partition coefficient
1,2,4-trimethylbenzene	3.63
95-63-6	
Xylene	3.15
1330-20-7	
Cumene	3.55
98-82-8	
Ethylbenzene	3.118
100-41-4	

Other adverse effects No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number D001

14. TRANSPORT INFORMATION

DOT Not regulated (If shipped in NON BULK packaging by ground transport)

UN number UN1866
UN proper shipping name Resin Solution

Transport hazard class(es) 3
Packing group |||

IATA

UN number UN1866 UN proper shipping name Resin Solution

Transport hazard class(es) 3
Packing group III

IMDG

UN number UN1866
UN proper shipping name Resin Solution

Transport hazard class(es) 3
Packing group | ||

15. REGULATORY INFORMATION

International Inventories

TSCA Complies
DSL/NDSL Complies

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No.	Weight-%	SARA 313 - Threshold Values %
1,2,4-trimethylbenzene - 95-63-6	95-63-6	3 - 7	1.0
Xylene - 1330-20-7	1330-20-7	1 - 5	1.0
Ethylbenzene - 100-41-4	100-41-4	0.1 - 1	0.1

SARA 311/312 Hazard Categories

Acute health hazard Yes
Chronic Health Hazard No
Fire hazard Yes
Sudden release of pressure hazard No
Reactive Hazard No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylene 1330-20-7	100 lb	-	-	Х
Ethylbenzene 100-41-4	1000 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Xylene	100 lb	-	RQ 100 lb final RQ
1330-20-7			RQ 45.4 kg final RQ
Cumene	5000 lb	-	RQ 5000 lb final RQ
98-82-8			RQ 2270 kg final RQ
Ethylbenzene	1000 lb	-	RQ 1000 lb final RQ
100-41-4			RQ 454 kg final RQ

US State Regulations

California Proposition 65

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Mineral Spirits	X	-	-
64742-88-7			
1,2,4-trimethylbenzene	X	X	X
95-63-6			
Xylene	X	X	X

1330-20-7			
Cumene 98-82-8	X	X	Х
Ethylbenzene 100-41-4	X	X	Х

16. OTHER INFORMATION

NFPA Health hazards 2 Flammability 2 Instability 0 Physical and chemical

properties -

HMIS Health hazards 2 Flammability 2 Physical hazards 0 Personal protection X

Prepared By Regulatory Department

Issuing Date11-Nov-2014Revision date10-Aug-2018

Revision Note

SDS sections updated

4 6 7 8 15 Disclaimer

The information contained on the Safety Data Sheet has been compiled from data considered accurate. This data is believed to be reliable, but it must be pointed out that values for certain properties are known to vary from source to source. PROSOCO, Inc. expressly disclaims any warranty express or implied as well as any liability for any injury or loss arising from the use of this information or the materials described. This data is not to be construed as absolutely complete since additional data may be desirable when particular conditions or circumstances exist. It is the responsibility of the user to determine the best precautions necessary for the safe handling and use of this product for his unique application. This data relates only to the specific material designated and is not to be used in combination with any other material. Many federal and state regulations pertain directly or indirectly to the product's end use and disposal of containers and unused material. It is the purchaser's responsibility to familiarize himself with all applicable regulations.

End of Safety Data Sheet