

SAFETY DATA SHEET

Issue Date 01-May-2015

GS - 700

Revision Date 29-Apr-2015

Version 1

Brickform Gem-Seal 700 VOC

1. IDENTIFICATION

Product identifier	
Product Name	Brickform Gem-Seal 700 VOC
Other means of identification Product Code	GS - 700
Recommended use of the chemical	and restrictions on use
Recommended Use	Restricted to professional users.
Uses advised against	Consumer use
Details of the supplier of the safety	data sheet
Supplier Address	Manufacturer Address
Solomon Colors, Inc.	Solomon Colors, Inc.
4050 Color Plant Road	4050 Color Plant Road
Springfield, IL	Springfield, IL
62702	62702
Company Phone Number	800-624-0261 (US & Canada); 217-522-3112 (Outside North America)
24 Hour Emergency Phone Number	800-373-7542

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)


Acute toxicity - Inhalation (Dusts/Mists)	Category 4	
Skin corrosion/irritation	Category 2	
Serious eye damage/eye irritation	Category 2	
Germ cell mutagenicity	Category 1B	
Carcinogenicity	Category 1B	
Specific target organ toxicity (single	Category 3	
exposure)		
Specific target organ toxicity (repeated	Category 2	
exposure)		
Aspiration toxicity	Category 1	
Flammable liquids		Category 4

Label elements

Emergency Overview

Danger

Hazard statements Harmful if inhaled Causes skin irritation



Obtain special instructions before use Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required Use only outdoors or in a well-ventilated area Wash face, hands and any exposed skin thoroughly after handling Wear eye/face protection Do not breathe dust/fume/gas/mist/vapors/spray Keep away from heat/sparks/open flames/hot surfaces. - No smoking Keep cool

Precautionary Statements - Response

IF exposed or if you feel unwell: Call a POISON CENTER or doctor/physician

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention

IF ON SKIN: Wash with plenty of soap and water

If skin irritation occurs: Get medical advice/attention

Take off contaminated clothing and wash before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

In case of fire: Use CO2, dry chemical, or foam for extinction

Do NOT induce vomiting

Precautionary Statements - Storage Store locked up Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Other Information

- May be harmful if swallowed
- · May be harmful in contact with skin
- Toxic to aquatic life with long lasting effects
- Toxic to aquatic life

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No.	Weight-%	Trade Secret
Petroleum naphtha, light aromatic	64742-95-6	30-60	*
Xylene	1330-20-7	15-40	*

Ethylbenzene 100-41-4	5-10	*
-----------------------	------	---

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES			
Description of first aid measures			
General advice	In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).		
Eye contact	Do not rub affected area. In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice.		
Skin Contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. In the case of skin irritation or allergic reactions see a physician.		
Inhalation	Move to fresh air in case of accidental inhalation of vapors or decomposition products. If breathing is irregular or stopped, administer artificial respiration. If symptoms persist, call a physician.		
Ingestion	If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.		
Most important symptoms and effects, both acute and delayed			
Symptoms	No information available.		
Indication of any immediate medical attention and special treatment needed			
Note to physicians	Treat symptomatically.		
5. FIRE-FIGHTING MEASURES			

Suitable extinguishing media

Dry chemical, Carbon Dioxide, Foam, Sand.

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

Specific hazards arising from the chemical

In the event of fire, cool tanks with water spray.

Hazardous combustion productsNo information available.

Explosion data Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautionsAvoid contact with skin, eyes or clothing. Use personal protective equipment as required.
Ensure adequate ventilation, especially in confined areas.

Other Information	ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). All equipment used when handling the product must be grounded. Use personal protective equipment as required.		
Environmental precautions			
Environmental precautions	See Section 12 for additional ecological information.		
Methods and material for containm	ent and cleaning up		
Methods for containment	Prevent further leakage or spillage if safe to do so. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).		
Methods for cleaning up	Use clean non-sparking tools to collect absorbed material. Ground and bond containers when transferring material. Dike to collect large liquid spills.		
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.		
	7. HANDLING AND STORAGE		
Precautions for safe handling	7. HANDLING AND STORAGE		
<u>Precautions for safe handling</u> Advice on safe handling	7. HANDLING AND STORAGE Handle in accordance with good industrial hygiene and safety practice. Use personal protective equipment as required. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded. Never pierce, drill, grind, cut, saw or weld any empty container.		
	Handle in accordance with good industrial hygiene and safety practice. Use personal protective equipment as required. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded. Never pierce, drill, grind, cut, saw or weld any empty container.		
Advice on safe handling	Handle in accordance with good industrial hygiene and safety practice. Use personal protective equipment as required. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be grounded. Never pierce, drill, grind, cut, saw or weld any empty container.		

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH	
Xylene	STEL: 150 ppm	TWA: 100 ppm	-	
1330-20-7	TWA: 100 ppm	TWA: 435 mg/m ³		
		(vacated) TWA: 100 ppm		
		(vacated) TWA: 435 mg/m ³		
		(vacated) STEL: 150 ppm		
		(vacated) STEL: 655 mg/m ³		
Ethylbenzene	TWA: 20 ppm	TWA: 100 ppm	IDLH: 800 ppm	
100-41-4		TWA: 435 mg/m ³	TWA: 100 ppm	
		(vacated) TWA: 100 ppm	TWA: 435 mg/m ³	
		(vacated) TWA: 435 mg/m ³	STEL: 125 ppm	
		(vacated) STEL: 125 ppm	STEL: 545 mg/m ³	
		(vacated) STEL: 545 mg/m ³		
ther Information	Vacated limits revoked 962 (11th Cir., 1992).	by the Court of Appeals decision in	AFL-CIO v. OSHA, 965 F.2d	
ngineering Controls	Showers			
	Eyewash stations			
	Ventilation systems.			
dividual protection measures, s	uch as personal protectiv	<u>e equipment</u>		
Eye/face protection	Avoid contact with eyes. Wear safety glasses with side shields (or goggles).			
Skin and body protection	Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.			
Respiratory protection	If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.			
		Do not eat, drink or smoke when using this product. Handle in accordance with good industrial hygiene and safety practice.		
eneral Hygiene Considerations			in accordance with good	

Information on basic physical and chemical properties

Liquid Viscous Colorless	Odor Odor threshold	Solvent No information available
<u>Values</u>	Remarks • Method	
	ASTM D56	
No information available		
No information available		
No information available		
-	insoluble	
	Viscous Colorless <u>Values</u> No information available 132.1 °C / 269.7 °F 60 °C / 140 °F No information available No information available No information available No information available No information available No information available No information available	Viscous Colorless Odor Odor threshold Values Remarks • Method No information available 132.1 °C / 269.7 °F 132.1 °C / 269.7 °F ASTM D86 60 °C / 140 °F ASTM D56 No information available No information available No information available No information available

Solubility in other solvents Partition coefficient Autoignition temperature Decomposition temperature Kinematic viscosity Dynamic viscosity Explosive properties Oxidizing properties

Other Information

Softening point Molecular weight VOC Content (%) Density Bulk density No information available No information available

No information available No information available <700 g/L No information available No information available

10. STABILITY AND REACTIVITY

Reactivity No data available

<u>Chemical stability</u> Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous polymerization

Hazardous polymerization does not occur.

<u>Conditions to avoid</u> Extremes of temperature and direct sunlight.

Incompatible materials

Strong oxidizing agents.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	Harmful by inhalation, in contact with skin and if swallowed
Inhalation	Avoid breathing vapors or mists. Harmful by inhalation.
Eye contact	Avoid contact with eyes. Risk of serious damage to eyes.
Skin Contact	Prolonged contact may cause redness and irritation.
Ingestion	Not an expected route of exposure. Harmful if swallowed.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Petroleum naphtha, light aromatic	= 8400 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 3400 ppm (Rat) 4 h
64742-95-6			
Xylene	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit) > 1700	= 29.08 mg/L (Rat) 4 h = 5000
1330-20-7		mg/kg (Rabbit)	ppm(Rat)4 h
Ethylbenzene	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.4 mg/L (Rat) 4 h
100-41-4	· ·		

Information on toxicological effects

Symptoms

No i	informat	ion ava	ailable.
------	----------	---------	----------

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization Germ cell mutagenicity Carcinogenicity	No informatio No informatio The table be		agency has listed any in	gredient as a carcinogen.
Chemical Name	ACGIH	IARC	NTP	OSHA
Xylene 1330-20-7	-	Group 3	-	-
Ethylbenzene 100-41-4	A3	Group 2B	-	Х
A3 - Animal Carcinogen IARC (International Age Group 3 - Not Classifiable OSHA (Occupational Sa X - Present	-	er) mans ttion of the US Department o	f Labor)	
Reproductive toxicity STOT - single exposure STOT - repeated exposur Target Organ Effects Aspiration hazard		on available. on available. ous system, Eyes, Respirat	tory system, Skin.	

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral)	4277 mg/kg
ATEmix (dermal)	2274 mg/kg
ATEmix (inhalation-dust/mist)	4.8 mg/l

12. ECOLOGICAL INFORMATION

Ecotoxicity

Persistence and degradability No information available.

Bioaccumulation

No information available.

Chemical Name	Partition coefficient
Xylene 1330-20-7	2.77 - 3.15
Ethylbenzene 100-41-4	3.2

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods	
Disposal of wastes	Disposal should be in accordance with applicable regional, national and local laws and regulations.
Contaminated packaging	Do not reuse container.
US EPA Waste Number	U220 U239

Chemical Name	California Hazardous Waste Status
Xylene	Toxic
1330-20-7	Ignitable
Ethylbenzene	Toxic
100-41-4	Ignitable

14. TRANSPORT INFORMATION

DOT

UN/ID no.	UN 1263
Proper shipping name	Paint Related Material
Hazard Class	3
Packing Group	III
Emergency Response Guide	128
Number	

15. REGULATORY INFORMATION

International Inventories TSCA DSL/NDSL EINECS/ELINCS ENCS IECSC KECL PICCS AICS

Complies Complies Does not comply Does not comply Complies Complies Complies Complies

Legend:

 TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

 DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

 EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

 ENCS - Japan Existing and New Chemical Substances

 IECSC - China Inventory of Existing Chemical Substances

 KECL - Korean Existing and Evaluated Chemical Substances

 PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute health hazard	No
Chronic Health Hazard	No
Fire hazard	Yes
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylene 1330-20-7	100 lb	-	-	Х
Ethylbenzene 100-41-4	1000 lb	Х	Х	Х

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Xylene	100 lb	-	RQ 100 lb final RQ
1330-20-7			RQ 45.4 kg final RQ
Ethylbenzene	1000 lb	-	RQ 1000 lb final RQ
100-41-4			RQ 454 kg final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

U.S. State Right-to-Know Regulations

16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA_	Flammability 2	Reactivity 0	Physical and Chemical <u>HMIS</u> Properties -
Health hazards 2	Flammability 2	Physical hazards 0	Personal protection G
Issue Date	01-May-2015		
Revision Date	29-Apr-201	5	

Issue Date Revision Date Revision Note Initial conversion to SDS

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet