

# **SAFETY DATA SHEET**

Issue Date 15-May-2015 Revision Date 30-Apr-2015 Version 1

PS-650 Poly Seal 650

#### 1. IDENTIFICATION

**Product identifier** 

Product Name Poly Seal 650

Other means of identification

Product Code PS-650

Recommended use of the chemical and restrictions on use

**Recommended Use** Restricted to professional users.

Uses advised against Consumer use

Details of the supplier of the safety data sheet

Supplier AddressManufacturer AddressSolomon Colors, Inc.Solomon Colors, Inc.4050 Color Plant Road4050 Color Plant RoadSpringfield, IL 62702Springfield, IL 62702

Company Phone Number 800-624-0261 (US & Canada); 217-522-3112 (Outside North America)

24 Hour Emergency Phone Number 800-373-7542

# 2. HAZARDS IDENTIFICATION

### Classification

#### **OSHA Regulatory Status**

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

| Skin corrosion/irritation              | Category 2  |            |
|--|-------------|------------|
| Serious eye damage/eye irritation      | Category 2  |            |
| Germ cell mutagenicity                 | Category 1B |            |
| Carcinogenicity                        | Category 1B |            |
| Specific target organ toxicity (single | Category 3  |            |
| exposure)                              |             |            |
| Aspiration toxicity                    | Category 1  |            |
| Flammable liquids                      | _           | Category 2 |

#### **Label elements**

| Emergency Overview |  |  |  |
|--------------------|--|--|--|
| Danger             |  |  |  |
|                    |  |  |  |

#### **Hazard statements**

Causes skin irritation

Causes serious eye irritation

May cause genetic defects

May cause cancer

May cause drowsiness or dizziness

May be fatal if swallowed and enters airways

Highly flammable liquid and vapor



Appearance Clear liquid

Physical state Liquid

**Odor** Aromatic

#### **Precautionary Statements - Prevention**

Obtain special instructions before use

Do not handle until all safety precautions have been read and understood

Use personal protective equipment as required

Wash face, hands and any exposed skin thoroughly after handling

Wear eye/face protection

Avoid breathing dust/fume/gas/mist/vapors/spray

Use only outdoors or in a well-ventilated area

Keep away from heat/sparks/open flames/hot surfaces. - No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

#### **Precautionary Statements - Response**

IF exposed or concerned: Get medical advice/attention

Specific treatment (see TEST on this label)

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

If skin irritation occurs: Get medical advice/attention

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Wash contaminated clothing before reuse

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician

Do NOT induce vomiting

In case of fire: Use CO2, dry chemical, or foam for extinction

#### **Precautionary Statements - Storage**

Store locked up

Store in a well-ventilated place. Keep container tightly closed

#### **Precautionary Statements - Disposal**

Dispose of contents/container to an approved waste disposal plant

#### Hazards not otherwise classified (HNOC)

#### Other Information

- · May be harmful if swallowed
- · May be harmful in contact with skin
- · Toxic to aquatic life with long lasting effects
- · Harmful to aquatic life

PS-650 2 / 11 Poly Seal 650

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

| Chemical Name                      | CAS No.     | Weight-% | Trade Secret |
|------------------------------------|-------------|----------|--------------|
| Proprietary Aromatic Solvent Blend | Proprietary | 10-45    | *            |
| Acetone                            | 67-64-1     | 15-45    | *            |
| Xylenes (o-, m-, p- isomers)       | 1330-20-7   | 10-45    | *            |
| Ethylbenzene                       | 100-41-4    | 5-25     | *            |

<sup>\*</sup>The exact percentage (concentration) of composition has been withheld as a trade secret.

# 4. FIRST AID MEASURES

#### Description of first aid measures

General advice In case of accident or unwellness, seek medical advice immediately (show directions for

use or safety data sheet if possible).

Eye contact Do not rub affected area. In the case of contact with eyes, rinse immediately with plenty of

water and seek medical advice.

Skin Contact Wash off immediately with soap and plenty of water while removing all contaminated

clothes and shoes. In the case of skin irritation or allergic reactions see a physician.

**Inhalation** Move to fresh air in case of accidental inhalation of vapors or decomposition products. If

breathing is irregular or stopped, administer artificial respiration. If symptoms persist, call a

physician.

Ingestion If swallowed, do not induce vomiting: seek medical advice immediately and show this

container or label.

Most important symptoms and effects, both acute and delayed

**Symptoms** No information available.

Indication of any immediate medical attention and special treatment needed

# 5. FIRE-FIGHTING MEASURES

#### Suitable extinguishing media

Dry chemical, Carbon Dioxide, Foam, Sand.

Unsuitable extinguishing media Caution: Use of water spray when fighting fire may be inefficient.

#### Specific hazards arising from the chemical

In the event of fire, cool tanks with water spray.

**Explosion data** 

Sensitivity to Mechanical Impact None. Sensitivity to Static Discharge None.

#### Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

#### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

**Personal precautions** Avoid contact with skin, eyes or clothing. Ensure adequate ventilation, especially in

confined areas.

Other Information ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

All equipment used when handling the product must be grounded. Use personal protective

equipment as required.

**Environmental precautions** 

**Environmental precautions** See Section 12 for additional ecological information.

Methods and material for containment and cleaning up

**Methods for containment** Prevent further leakage or spillage if safe to do so. Contain and collect spillage with

non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see Section 13).

Methods for cleaning up

Use clean non-sparking tools to collect material and place it into loosely covered plastic

containers for later disposal. Ground and bond containers when transferring material. Dike

for later disposal and cover with wet sand or earth.

**Prevention of secondary hazards** Clean contaminated objects and areas thoroughly observing environmental regulations.

#### 7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling

Handle in accordance with good industrial hygiene and safety practice. Use personal

protective equipment as required. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Use spark-proof tools and explosion-proof equipment. All equipment used when handling the product must be

grounded. Never pierce, drill, grind, cut, saw or weld any empty container.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric

motors and static electricity). Keep containers tightly closed in a cool, well-ventilated place. Do not store near combustible materials. Use spark-proof tools and explosion-proof

equipment.

**Incompatible materials** Strong oxidizing agents.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

**Exposure Guidelines** 

| Chemical Name                | ACGIH TLV     | OSHA PEL                                   | NIOSH IDLH                  |
|------------------------------|---------------|--|-----------------------------|
| Acetone                      | STEL: 750 ppm | TWA: 1000 ppm                              | IDLH: 2500 ppm              |
| 67-64-1                      | TWA: 500 ppm  | TWA: 2400 mg/m <sup>3</sup>                | TWA: 250 ppm                |
|                              |               | (vacated) TWA: 750 ppm                     | TWA: 590 mg/m <sup>3</sup>  |
|                              |               | (vacated) TWA: 1800 mg/m <sup>3</sup>      |                             |
|                              |               | (vacated) STEL: 2400 mg/m <sup>3</sup> The |                             |
|                              |               | acetone STEL does not apply to the         |                             |
|                              |               | cellulose acetate fiber industry. It is    |                             |
|                              |               | in effect for all other sectors            |                             |
|                              |               | (vacated) STEL: 1000 ppm                   |                             |
| Xylenes (o-, m-, p- isomers) | STEL: 150 ppm | TWA: 100 ppm                               | =                           |
| 1330-20-7                    | TWA: 100 ppm  | TWA: 435 mg/m <sup>3</sup>                 |                             |
|                              |               | (vacated) TWA: 100 ppm                     |                             |
|                              |               | (vacated) TWA: 435 mg/m <sup>3</sup>       |                             |
|                              |               | (vacated) STEL: 150 ppm                    |                             |
|                              |               | (vacated) STEL: 655 mg/m <sup>3</sup>      |                             |
| Ethylbenzene                 | TWA: 20 ppm   | TWA: 100 ppm                               | IDLH: 800 ppm               |
| 100-41-4                     |               | TWA: 435 mg/m <sup>3</sup>                 | TWA: 100 ppm                |
|                              |               | (vacated) TWA: 100 ppm                     | TWA: 435 mg/m <sup>3</sup>  |
|                              |               | (vacated) TWA: 435 mg/m <sup>3</sup>       | STEL: 125 ppm               |
|                              |               | (vacated) STEL: 125 ppm                    | STEL: 545 mg/m <sup>3</sup> |
|                              |               | (vacated) STEL: 545 mg/m <sup>3</sup>      | _                           |

NIOSH IDLH Immediately Dangerous to Life or Health

Other Information Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d

962 (11th Cir., 1992).

**Appropriate engineering controls** 

Engineering Controls Showers

Eyewash stations Ventilation systems.

Individual protection measures, such as personal protective equipment

**Eye/face protection** Avoid contact with eyes. Wear safety glasses with side shields (or goggles).

**Skin and body protection**Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls,

as appropriate, to prevent skin contact.

Respiratory protection If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved

respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be

provided in accordance with current local regulations.

General Hygiene Considerations Do not eat, drink or smoke when using this product. Handle in accordance with good

industrial hygiene and safety practice.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Liquid Appearance Clear liquid

AppearanceClear liquidOdorAromaticColorColorlessOdor thresholdNo information available

Property Values Remarks • Method

pH No information available

Melting point/freezing point No information available

PS-650 5 / 11 Poly Seal 650

Boiling point / boiling range No information available °C / 131.5

٥F

Flash point 21.7 °C / 71 °F
Evaporation rate No information available
Flammability (solid, gas) No information available

Flammability Limit in Air

Upper flammability limit: No information available Lower flammability limit: No information available Vapor pressure No information available Vapor density No information available **Specific Gravity** No information available Water solubility No information available Solubility in other solvents No information available Partition coefficient No information available **Autoignition temperature** No information available **Decomposition temperature** No information available No information available Kinematic viscosity **Dynamic viscosity** No information available **Explosive properties** No information available **Oxidizing properties** No information available

#### **Other Information**

Softening point No information available Molecular weight No information available

**VOC Content (%)** < 650 g/L

Density

No information available

No information available

# 10. STABILITY AND REACTIVITY

#### Reactivity

No data available

## **Chemical stability**

Stable under recommended storage conditions.

## **Possibility of Hazardous Reactions**

None under normal processing.

#### **Conditions to avoid**

Extremes of temperature and direct sunlight.

#### **Incompatible materials**

Strong oxidizing agents.

# **Hazardous Decomposition Products**

None known based on information supplied.

#### 11. TOXICOLOGICAL INFORMATION

#### Information on likely routes of exposure

Product Information Harmful by inhalation, in contact with skin and if swallowed

**Inhalation** Avoid breathing vapors or mists. Harmful by inhalation.

**Eye contact** Avoid contact with eyes. Risk of serious damage to eyes.

**Skin Contact** Prolonged contact may cause redness and irritation.

**Ingestion** Do not taste or swallow. Harmful if swallowed.

| Chemical Name                             | Oral LD50          | Dermal LD50              | Inhalation LC50                                |
|---|--------------------|--------------------------|--|
| Proprietary Aromatic Solvent Blend        | = 8400 mg/kg (Rat) | > 2000 mg/kg (Rabbit)    | = 3400 ppm (Rat) 4 h                           |
| Acetone<br>67-64-1                        | = 5800 mg/kg (Rat) | -                        | = 50100 mg/m³ (Rat) 8 h                        |
| Xylenes (o-, m-, p- isomers)<br>1330-20-7 | = 4300 mg/kg (Rat) | > 1700 mg/kg(Rabbit)     | = 47635 mg/L (Rat) 4 h = 5000<br>ppm (Rat) 4 h |
| Ethylbenzene<br>100-41-4                  | = 3500 mg/kg (Rat) | = 15354 mg/kg ( Rabbit ) | = 17.2 mg/L (Rat) 4 h                          |

# Information on toxicological effects

Symptoms No information available.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

SensitizationNo information available.Germ cell mutagenicityNo information available.CarcinogenicityNo information available.

| Chemical Name                             | ACGIH | IARC     | NTP | OSHA |
|---|-------|----------|-----|------|
| Xylenes (o-, m-, p- isomers)<br>1330-20-7 | -     | Group 3  | -   | -    |
| Ethylbenzene<br>100-41-4                  | A3    | Group 2B | -   | X    |

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Not classifiable as a human carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity
STOT - single exposure
STOT - repeated exposure
No information available.
No information available.

Target Organ Effects Central nervous system, Eyes, Respiratory system, Skin.

Aspiration hazard No information available.

#### Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 4568 mg/kg
ATEmix (dermal) 3859 mg/kg
ATEmix (inhalation-dust/mist) 5.8 mg/l

# 12. ECOLOGICAL INFORMATION

# **Ecotoxicity**

| Chemical Name                      | Algae/aquatic plants  | Fish  | Crustacea                          |
|------------------------------------|---|---|------------------------------------|
| Proprietary Aromatic Solvent Blend | -   | 9.22: 96 h Oncorhynchus mykiss                            | 6.14: 48 h Daphnia magna mg/L      |
|                                    |   | mg/L LC50   | EC50                               |
| Acetone                            | <del>-</del>  | 4.74 - 6.33: 96 h Oncorhynchus                            | 10294 - 17704: 48 h Daphnia        |
| 67-64-1                            |   | mykiss mL/L LC50 8300: 96 h                               | magna mg/L EC50 Static 12600 -     |
|                                    |   | Lepomis macrochirus mg/L LC50                             | 12700: 48 h Daphnia magna mg/L     |
|                                    |   | 6210 - 8120: 96 h Pimephales                              | EC50                               |
|                                    |   | promelas mg/L LC50 static                                 |                                    |
| Xylenes (o-, m-, p- isomers)       | -   | 13.4: 96 h Pimephales promelas                            | 3.82: 48 h water flea mg/L EC50    |
| 1330-20-7                          |   | mg/L LC50 flow-through 2.661 -                            | 0.6: 48 h Gammarus lacustris mg/L  |
|                                    |   | 4.093: 96 h Oncorhynchus mykiss                           | LC50                               |
|                                    |   | mg/L LC50 static 13.5 - 17.3: 96 h                        |                                    |
|                                    |   | Oncorhynchus mykiss mg/L LC50                             |                                    |
|                                    |   | 780: 96 h Cyprinus carpio mg/L                            |                                    |
|                                    |   | LC50 semi-static 780: 96 h Cyprinus                       |                                    |
|                                    |   | carpio mg/L LC50 13.1 - 16.5: 96 h                        |                                    |
|                                    |   | Lepomis macrochirus mg/L LC50                             |                                    |
|                                    |   | flow-through 19: 96 h Lepomis                             |                                    |
|                                    |   | macrochirus mg/L LC50 7.711 -                             |                                    |
|                                    |   | 9.591: 96 h Lepomis macrochirus                           |                                    |
|                                    |   | mg/L LC50 static 23.53 - 29.97: 96                        |                                    |
|                                    |   | h Pimephales promelas mg/L LC50                           |                                    |
|                                    |   | static 30.26 - 40.75: 96 h Poecilia                       |                                    |
| F. I. II                           | 40 70 LD  | reticulata mg/L LC50 static                               | 10.01.101.0                        |
| Ethylbenzene                       | 4.6: 72 h Pseudokirchneriella                                 | 11.0 - 18.0: 96 h Oncorhynchus                            | 1.8 - 2.4: 48 h Daphnia magna mg/L |
| 100-41-4                           | subcapitata mg/L EC50 438: 96 h                               | mykiss mg/L LC50 static 4.2: 96 h                         | EC50                               |
|                                    | Pseudokirchneriella subcapitata                               | Oncorhynchus mykiss mg/L LC50 semi-static 7.55 - 11: 96 h |                                    |
|                                    | mg/L EC50 2.6 - 11.3: 72 h<br>Pseudokirchneriella subcapitata | Pimephales promelas mg/L LC50                             |                                    |
|                                    | mg/L EC50 static 1.7 - 7.6: 96 h                              | flow-through 32: 96 h Lepomis                             |                                    |
|                                    | Pseudokirchneriella subcapitata                               | macrochirus mg/L LC50 static 9.1 -                        |                                    |
|                                    | mg/L EC50 static  | 15.6: 96 h Pimephales promelas                            |                                    |
|                                    | mg/L LOSO static  | mg/L LC50 static 9.6: 96 h Poecilia                       |                                    |
|                                    |   | reticulata mg/L LC50 static                               |                                    |
|                                    |   | Totadulata mg/L LOGO static                               |                                    |

# Persistence and degradability No information available.

# **Bioaccumulation**

No information available.

| Chemical Name                             | Partition coefficient |
|---|-----------------------|
| Acetone<br>67-64-1                        | -0.24                 |
| Xylenes (o-, m-, p- isomers)<br>1330-20-7 | 2.77 - 3.15           |
| Ethylbenzene<br>100-41-4                  | 3.118                 |

Other adverse effects

No information available

# 13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal of wastes Disposal should be in accordance with applicable regional, national and local laws and

regulations.

Contaminated packaging Do not reuse container.

US EPA Waste Number D001 U002 U239

| Chemical Name                             | RCRA | RCRA - Basis for Listing          | RCRA - D Series Wastes | RCRA - U Series Wastes |
|---|------|-----------------------------------|------------------------|------------------------|
| Acetone<br>67-64-1                        | -    | Included in waste stream:<br>F039 | -                      | U002                   |
| Xylenes (o-, m-, p- isomers)<br>1330-20-7 | -    | Included in waste stream:<br>F039 | -                      | U239                   |
| Ethylbenzene<br>100-41-4                  | -    | Included in waste stream:<br>F039 | -                      | -                      |

| Chemical Name                | California Hazardous Waste Status |
|------------------------------|-----------------------------------|
| Acetone<br>67-64-1           | Ignitable                         |
| Xylenes (o-, m-, p- isomers) | Toxic                             |
| 1330-20-7                    | Ignitable                         |
| Ethylbenzene                 | Toxic                             |
| 100-41-4                     | Ignitable                         |

# 14. TRANSPORT INFORMATION

DOT

**UN/ID no.** UN 1263

Proper shipping name Paint Related Material

Hazard Class 3
Packing Group II
Emergency Response Guide 128

Number

#### 15. REGULATORY INFORMATION

#### **International Inventories**

**TSCA** Complies **DSL/NDSL** Complies Does not comply **EINECS/ELINCS ENCS** Complies Complies **IECSC** Complies **KECL PICCS** Complies **AICS** Complies

#### Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

**ENCS** - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

**KECL** - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

#### **US Federal Regulations**

#### **SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

| Chemical Name                            | SARA 313 - Threshold Values % |
|--|-------------------------------|
| Xylenes (o-, m-, p- isomers) - 1330-20-7 | 1.0                           |
| Ethylbenzene - 100-41-4                  | 0.1                           |

#### SARA 311/312 Hazard Categories

| Acute health hazard               | No |
|-----------------------------------|----|
| Chronic Health Hazard             | No |
| Fire hazard                       | No |
| Sudden release of pressure hazard | No |
| Reactive Hazard                   | No |

#### **CWA (Clean Water Act)**

| Chemical Name                             | CWA - Reportable<br>Quantities | CWA - Toxic Pollutants | CWA - Priority Pollutants | CWA - Hazardous<br>Substances |
|---|--------------------------------|------------------------|---------------------------|-------------------------------|
| Xylenes (o-, m-, p- isomers)<br>1330-20-7 | 100 lb                         | -                      | -                         | Х                             |
| Ethylbenzene<br>100-41-4                  | 1000 lb                        | Х                      | X                         | Х                             |

#### **CERCLA**

| Chemical Name                             | Hazardous Substances RQs | CERCLA/SARA RQ | Reportable Quantity (RQ)                   |
|---|--------------------------|----------------|--|
| Acetone<br>67-64-1                        | 5000 lb                  | -              | RQ 5000 lb final RQ<br>RQ 2270 kg final RQ |
| Xylenes (o-, m-, p- isomers)<br>1330-20-7 | 100 lb                   | -              | RQ 100 lb final RQ<br>RQ 45.4 kg final RQ  |
| Ethylbenzene<br>100-41-4                  | 1000 lb                  | -              | RQ 1000 lb final RQ<br>RQ 454 kg final RQ  |

#### **US State Regulations**

#### **California Proposition 65**

This product contains the following Proposition 65 chemicals

| Chemical Name |                         | California Proposition 65 |  |
|---------------|-------------------------|---------------------------|--|
|               | Ethylbenzene - 100-41-4 | Carcinogen                |  |

PS-650 10 / 11 Poly Seal 650

#### U.S. State Right-to-Know Regulations

| Chemical Name                             | New Jersey | Massachusetts | Pennsylvania |
|---|------------|---------------|--------------|
| Acetone<br>67-64-1                        | Х          | X             | X            |
| Xylenes (o-, m-, p- isomers)<br>1330-20-7 | X          | X             | Х            |
| Ethylbenzene<br>100-41-4                  | Х          | X             | X            |

# 16. OTHER INFORMATION, INCLUDING DATE OF PREPARATION OF THE LAST REVISION

NFPA Reactivity 0 Physical and Chemical HMIS Health hazards 0

Properties -

Flammability 0 Physical hazards 0 Personal protection X

Issue Date15-May-2015Revision Date30-Apr-2015

**Revision Note** 

No information available

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**